



(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
24 October 2002 (24.10.2002)

PCT

(10) International Publication Number
WO 02/083591 A1

(51) International Patent Classification: C04B 7/36

(21) International Application Number: PCT/CA02/00517

(22) International Filing Date: 12 April 2002 (12.04.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/283,327 13 April 2001 (13.04.2001) US

(71) Applicant (for all designated States except US): CO2 SOLUTION INC. [CA/CA]; 1091, Boulevard Pie XI Sud, Val-Bélair, Québec G3K 1J9 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LALANDE, Jean-Marie [CA/CA]; 6545 St-Laurent, Apartment 201, Lévis, Québec G6V 3N9 (CA). TREMBLAY, Anne [CA/CA]; 251 Rue Delage, Apartment 214, Beauport, Québec G1V 6C4 (CA).

(74) Agent: ROBIC; 55, rue St-Jacques, Montréal, Québec H2Y 3X2 (CA).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GH, GM, GR, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A PROCESS AND A PLANT FOR THE PRODUCTION OF PORTLAND CEMENT CLINKER

(57) Abstract: A process is disclosed for producing cement clinker, comprising the steps of: a) providing a mixture of ground calcareous materials and ground argillaceous materials; b) heating the mixture of step a) to a temperature sufficient to calcine and fuse the ground materials to form the cement clinker, and thereby producing an exhaust gas containing CO₂; c) catalysing the hydration of at least a portion of the CO₂ contained in the exhaust gas and producing a solution containing bicarbonate ions and hydrogen ions; and d) adding to the solution obtained in step c) metal ions, and adjusting the pH of the solution to precipitate a carbonate of said metal. Preferably, the metal ions are Ca²⁺ obtained from the dissolution of a material selected from the group consisting of CaCl₂, cement kiln dust and sea salts and the carbonate is CaCO₃, which is advantageously recycled into the process by adding the CaCO₃ to the mixture of step a). A cement plant for performing this process is also disclosed.

WO 02/083591 A1

A PROCESS AND A PLANT FOR THE PRODUCTION OF PORTLAND CEMENT CLINKER

FIELD OF THE INVENTION

- 5 The present invention relates generally to the field of processes and apparatuses for the production of Portland cement clinker. More specifically, it concerns a process and a plant for the recovery and recycling of the carbon dioxide emissions from the production of Portland cement clinker.

BACKGROUND

- 10 Preserving the environment goes above all through the recognition of polluting agents, a list stretching out every year. Carbon dioxide is a by-product of many industrial chemical reactions and is considered polluting only of late. Until recently still, it was rather seen as a consequence of no gravity from the combustion of carbonated compounds such as coal and petroleum, or else, as a desired final product in the control of gaseous emissions.
- 15 Accumulation of evidences as to the participation of CO₂ in the greenhouse effect responsible for earth's global warming revealed a problematic of extreme urgency. On this account, international engagements proposed in Kyoto (Kyoto protocol, 1997) have commanded for active research in reducing greenhouse effect gases, particularly CO₂.
- 20 Amongst the finger pointed industries, cement fabrics account for 8 % of the CO₂ planetary anthropic emissions. Portland cement is made of lime, alumina, iron and silica. This mixture is pulverized and fused together by burning at high heat (more than 1,400°C) in a rotary kiln. Combining the resulting material, called "clinker", with gypsum, results in the production of a fine powder known as Portland cement. In the
- 25 production process, carbon dioxide emissions come from fossil fuel combustion and a calcination stage of limestone (CaCO₃).

Portland cement is the binding agent that enables the formation of concrete, which will also include aggregates, air and water.

- Portland cement is the result of a chemical combination of calcium (usually from limestone), silica (clay, sand and shale), alumina (bauxite), iron (ore) and small amounts of various chemicals called admixtures to which gypsum is added at the last grinding in order to control the cement setting process.

The production of one tonne of cement (2000) requires close to 3 500 tonnes of raw materials. Lime and silica account for approximately 85 % of the weight.

- Two main categories of production processes are in use in this industry : the dry process kiln (70 % in the U.S.) and the wet process kiln (older). For both processes, the first step is similar. The raw materials are crushed for reduction to about 3 inches or smaller. In the wet process, the raw materials, properly proportioned, are then ground with water, thoroughly mixed in the form of slurry. In the dry process, raw materials are ground and mixed in a dry state. In both processes, the slurry or the dry material is fed to a rotary kiln inclined slightly from the horizontal where it is heated to more than 1,400 °C.

A rotary kiln is frequently as much as 12 feet in diameter and 400 feet long.

- The "raw meal" is fed into the higher end of the kiln and progresses to the lower end, moved by the rotation. On its way down, the "raw meal" is facing a burner blowing its flame under an upward forced draft.

At the lower end, the new substance, called clinker, is formed in pieces about the size of marbles. The heat is recuperated from the cooling of the red-hot clinker and returned to the kiln. The clinker remains to be ground into fine powder to which some gypsum is added to form cement.

- Cement is then put in bags or carried in bulk to ready mix plants. Concrete is produced by mixing cement with fine (sand) or coarse aggregates (gravel or crushed

stone) and water. Often, some chemicals are added to control setting time and plasticity.

The first important reaction to occur is the calcining of limestone (calcium carbonate CaCO_3) into lime (calcium oxide CaO) and carbon dioxide (CO_2) at a temperature of 1 650 °F (900 °C).

The second reaction is the bonding of calcium oxide and silicates to form calcium silicates. Small amounts of calcium aluminate and calcium aluminoferrite are also formed. The relative proportions of these compounds determine the key properties of the resultant Portland cement and the type classification.

1.0 Cement Kiln Dust (CKD)

Cement Kiln Dust (CKD), a fine granular material generated during cement production, is carried up by the combustion gases. The CKD is normally removed and collected by an air pollution control system. The collected CKD which is mainly made up of lime (CaO), K_2O , SO_3 , silica (SiO_2) and alumina (Al_2O_3) may be returned into the process or stocked.

The US Environmental Protection Agency published a report on the foreseeable costs of conforming to future regulations on CDK dust (EPA, 1998). Among the interesting information published in this report, is the ratio of CDK production relative to clinker production depending on Kiln type (Table 1). As it can be appreciated, wet processes generate a greater production of CKD (between 11 and 17 %).

Table 1 Average CKD production vs clinker production depending on Kiln type

Kiln Type	Mean CKD / clinker production
<i>Non-hazardous fuel kiln</i>	
Dry process	0,060
Dry preheating	0,024
Wet process	0,107
<i>Hazardous fuel kiln</i>	
Dry process	0,061

Kiln Type	Mean CKD / clinker production
Dry preheating	0,038
Wet process	0,166

The net CKD refuse (excluding CKD regenerated during the process) output by 110 US cement plants is approximately 3,3 million tonnes per year.

In the above-mentioned EPA study, the baselines and the costs relating to conforming to future regulations were calculated for every affected plant. The total before-tax baseline costs, the initial conformity costs and the annual conformity costs respectively amount to 54,9; 98,5 and 43,7 millions US\$. Out of 110 US plants, 68 (62 %) would incur average annual costs of 646 000 US\$, translating to 19,96 US\$ per CKD tonne and 1,12 US\$ per cement tonne produced. The total annual income for these 68 cement plants is estimated at 2,945 billion US\$. The cost of conforming to regulations would therefore represent 1,5 % of their income.

CO₂ emissions from cement Portland production

CO₂ emissions produced by cement production come from two sources:

1. Fossil fuel combustion required to heat the raw meal – 6 millions BTUs/tonne of cement produce $\frac{3}{4}$ tonne of CO₂.
2. Calcining of limestone into lime – $\frac{1}{2}$ tonne of CO₂/tonne of cement.

In Canada, one tonne of cement generates 0.5 tonne of CO₂ from limestone conversion and about 0.35 tonne of CO₂ from the combustion of fossil products, for a total of 0.85 tonne of CO₂ for each tonne of cement produced.

The very high temperatures required for cement production allow for burning all sorts of materials such as solvents, paint, and tires. At these temperatures, the combustion is complete and pollution is reduced to a minimum.

The methods already known in the art for reducing CO₂ emissions are the improvement of the energy efficiency of the process, the replacement of high carbon fuels by low carbon fuels, the use of waste as alternative fuel, the use of industrial waste containing lime and the use of fly ash to replace cement (15 to 35 %) in concrete. Fly ash is a by-product of the combustion of pulverized coal in thermal power plants.

Literature abounds with a good number of processes destined to reducing carbon dioxide emissions by the cement industry. US6,240,859; GB587101; US5,744,078 propose above all an improvement of combustion efficiencies and recycling of fly ashes as cement additive. Patent DE4032557 suggests a method of handling aggregates and cement claiming improved energetic efficiency and in this way, preventing CO₂ discharge by cement fabrics. Patent JP09-110485 uses absorption and volatilization of CO₂ to produce energy. Finally, European patent WO9966260 advises reutilization of industrial exhaust gas, thus achieving improved combustion efficiency.

Japanese patent 10-130045 discloses cement waste recycling in the fabrication of regenerated cement, by the way claiming a reduction of CO₂ emissions in the environment. As a matter of fact, combined recycling of CO₂ and manufacture residues is often invoked as a means for reducing cementous polluting waste (JP2000-239670; JP2000-119049; JP09-168775). In some configurations (US6,187,277; JP07-068164; JP2000-300983), recycled solid materials can be directly used for carbon dioxide fixation of industrial gas exhausts. Another Japanese patent (JP10-314758) was conceived so that CO₂ from the gaseous effluent of ceramic industries can be eliminated by introduction of residual water in cement plants.

CA1143910 describes a method allowing the use of CO₂ from a waste flue gas and some waste material for manufacturing an asbestos free fibre reinforced cement. A European untitled document (GB103290) also expects recycling of CO₂ for Portland cement manufacturing, in the same way as patent GB384060, which particularly uses a simple valve to isolate produced CO₂ from other flue gases during the

process.

Another way of reducing industrial CO₂ emissions consists of transforming this gas to synthesis products of commercial value. Patent JP2000-072981 suggests carbon black production by utilizing exhaust gas in cement production through CO₂ catalytic fixation whilst another (JP58-208117) allows for the manufacture of liquefied carbon dioxide from the waste gas of cement calcining kiln. Patent JP06-263665 deals with catalytic hydrogenation of carbon dioxide gas exhausted from cement factories for the production of chemicals such as methane and methanol.

A totally different approach preaches cement admixtures and compositions giving low loads on the environment and discharging smaller amounts of carbon dioxide, as it is the case for patents FR2669918 and JP2001-039751.

Currently, many scripts emanate from scientists with the purpose of reducing CO₂ emissions in general. Sinking CO₂ in the seawater over the deep ocean floor (US 5,364,611; US 5,304,356; US 5,293,751) persists amongst the main considerations despite the many uncertainties and inconveniences associated with this method. Chemical fixation (CA 2352969) and selective adsorption of CO₂ (US 5,667,561; JP02-000699) also stand amongst favoured methods in the literature. Membrane separation (JP11-235999) and chemical conversion in ether or methanol (US 6,248,795) offer interesting possibilities as well. One cannot help, but conclude exhaust gas absorption (US6,117,404; CA2255287; US5,888,256) remains one of the most promising methods and the very solubilization of concerned gases constitute the corner stone of all innovations in that field.

With this perspective, carbonic anhydrase has already been used for waste water treatment (US 6,110,370) and recently, for reducing CO₂ emissions in enzymatic photobioreactors (US 5,614,378). Carbonic anhydrase is a highly reactive enzyme observed in most animal and vegetal species and thus, readily available. Trachtenberg (US 6,143,556; CA 2222030) describes a system for gas processing with carbonic anhydrase without suggesting any specific application for cement fabrics. Michigan University introduced a photobioreactor for the conversion of CO₂

with carbonic anhydrase, however destined to medical use as an artificial lung for life support (WO 9200380; US 5,614,378).

US patent 6,258,335 unveiled a catalytic process for carbon dioxide removal of ice exhaust by chemical fixation. This technology includes the optional use of carbonic anhydrase without particular consideration for cement plants. US Patent (4,743,545) exposed a bioreactor with hollow beads including catalyst, the latter being carbonic anhydrase if needed.

US 4,602,987 and US 4,761,209 disclose a method for extraction and utilization of oxygen from fluids. This system conceived for oxygen recovering especially includes a step for carbon dioxide removal by carbonic anhydrase ().

EP0991462; AU7753398; WO9855210; CA2291785 in the name of the Applicant propose a countercurrent packed column bioreactor for treating carbon dioxide. In this process, carbonic anhydrase is used immobilized or in a free state.

Although a great deal of efforts have been made to reduce in general, the greenhouse effect caused by the emissions of CO₂, there is still a need for further improvements and that mainly in the field of cement clinker production.

SUMMARY OF THE INVENTION

An object of the present invention is to satisfy the above-mentioned need.

According to the present invention, there is provided a process for producing cement clinker, comprising the steps of: a) providing a mixture of ground calcareous materials and ground argillaceous materials; b) heating the mixture of step a) to a temperature sufficient to calcine and fuse the ground materials to form the cement clinker, and thereby producing an exhaust gas containing CO₂; c) catalysing the hydration of at least a portion of the CO₂ contained in the exhaust gas and producing a solution containing bicarbonate ions and hydrogen ions; and d) adding to the solution obtained in step c) metal ions, and adjusting the pH of the solution to

precipitate a carbonate of said metal.

- As can be appreciated, the process according to the invention allows the carbon dioxide emissions from the production of cement clinker to be greatly reduced and even eliminated by simply catalysing the hydration of CO_2 into a solution of bicarbonate ions and hydrogen ions. The bicarbonate ions are then reacted with
- 5 metals ions to precipitate a carbonated metal harmless to the environment.

The hydration is preferably performed in the presence of an enzyme capable of catalysing the hydration of dissolved CO_2 into hydrogen ions and bicarbonate ions. The enzyme is preferably carbonic anhydrase or an analogue thereof.

- Also preferably, the metal ions are Ca^{++} and the carbonate is CaCO_3 . In such a case, the process preferably comprises after step d), the step of: e) recycling the CaCO_3 obtained in step d) into the process by adding the CaCO_3 to the mixture of step a). Also in this case, the ions Ca^{++} are preferably obtained from the dissolution of a material selected from the group consisting of CaCl_2 , cement kiln dust and sea
- 10 salts.
- 15

According to another preferred aspect, step c) of catalisation comprises the steps of: feeding liquid H_2O and at least a portion of the exhaust gas into a bioreactor containing therein a reaction chamber filled with said carbonic anhydrase immobilized on a support.

- As can be appreciated, the process according to this preferred embodiment allows reduction of CO_2 emissions at the source through a recycling loop integrated into the cement plant. The loop mainly consists of gas/liquid CO_2 packed column absorption catalyzed by an immobilized enzyme (carbonic anhydrase) for the subsequent production of calcium carbonate (CaCO_3). The loop is completed when the calcium
- 20 carbonate is used as first class raw material for the fabrication of Portland cement.
- 25

According to this preferred aspect, the process has the advantages of recycling the CO_2 into the process and providing a first class raw material for the production of the

cement clinker.

The calcareous materials are preferably selected from the group consisting of limestone, marine shells and marl, and the argillaceous materials are preferably selected from the group consisting of clay, slate, sand, shale, and blast-furnace
5 slags.

Also preferably, the mixture of step a) further comprises one or more material selected from the group consisting of aluminium, iron and chemical admixture.

According to the present invention, there is also provided a plant for producing cement clinker, comprising: a kiln for burning raw materials suitable for producing
10 cement clinker, the kiln having an inlet for receiving the raw materials, an outlet for discharging the cement clinker and a gas outlet for discharging an exhaust gas containing CO_2 . The plant also comprises means for catalysing the hydration of the CO_2 contained in the exhaust gas into bicarbonate ions and hydrogen ions; and means for reacting the bicarbonate ions with metal ions to precipitate the carbonate
15 of said metal.

The metal ions are preferably Ca^{++} and the carbonate is preferably CaCO_3 . In such a case, the plant preferably further comprises means for transferring the precipitate CaCO_3 into the inlet of the kiln.

According to a preferred aspect of the invention, the means for catalysing the
20 hydration of the CO_2 comprises a bioreactor comprising a gas inlet for receiving at least a portion of the exhaust gas from the kiln; a liquid inlet for receiving an aqueous liquid, a reaction chamber in fluid communication with the gas inlet and the liquid inlet, the reaction chamber containing therein immobilized enzymes capable of catalysing the hydration of dissolved CO_2 into bicarbonate ions and hydrogen ions;
25 and a liquid outlet in fluid communication with the reaction chamber for discharging a solution of bicarbonate ions and hydrogen ions.

The means for reacting the bicarbonate ions with metal ions is preferably a reaction

reservoir.

Also preferably, the plant comprises cleansing means for cleansing the exhaust gas; means for transferring the exhaust gas from the kiln to the cleansing means; and means for transferring the clean exhaust gas from the cleansing means to the catalysing means.

The objects, advantages and other features of the present invention will become more apparent upon reading of the following non restrictive description of the preferred embodiment thereof, given for the purpose of exemplification only with reference to the accompanying drawings.

10 DESCRIPTION OF THE DRAWING

Figure 1 is a schematic flow chart of a process according to the invention.

DESCRIPTION OF A PREFERRED EMBODIMENT

The process according to a preferred embodiment of the invention comprises a step where the CO₂ emissions from the rotary kiln used in the cement production are transformed into bicarbonate ions by contacting the CO₂ gas emissions with an aqueous liquid in a bioreactor containing enzymes capable of catalysing the hydration of CO₂ into hydrogen and bicarbonate ions, and then reacting the bicarbonate ions with calcium ions so as to precipitate calcium carbonate (CaCO₃) and recycling the same as a first class raw material in the rotary kiln used for producing the Portland cement clinker. The enzyme used is preferably carbonic anhydrase, and it is used free or immobilized on an appropriate support.

Gaseous CO₂, considered the greatest contributor to the greenhouse effect, comes from the respiration of living organisms, fuel combustion and certain chemical reactions such as fossil fuel reforming. The CO₂ produced by the two latter sources may be enzymatically treated with the enzymatic system described in WO9855210

11.

in the name of the applicant. This enzymatic system is a process for the transformation of gaseous CO_2 into bicarbonate and hydrogen ions. The transformation reaction, usually a slow naturally occurring process, is catalyzed by an immobilized or free state enzyme in a specially made reactor. The enzymatic process catalyzes the hydration of dissolved carbon dioxide. The subsequent ionization equilibrium reaction produces bicarbonate and hydrogen ions. The following equations describe the relevant process :

Equation 1 Hydration : $\text{dissolved CO}_2 \rightarrow \text{H}_2\text{CO}_3$

Equation 2 Ionization : $\text{H}_2\text{CO}_3 \rightarrow \text{H}^+ + \text{HCO}_3^- \rightarrow \text{CO}_3^{2-} + \text{H}^+$

- 10 The carbonate ions, among others, are precipitated with calcium ions or others into carbonated mineral form.

Detailed description of a plant according to a preferred embodiment of the invention

Referring to figure 1, the plant (10) for the production of cement clinker comprises a kiln schematically represented as box (12) for burning raw materials suitable for producing cement clinker. As commonly used in the production of cement clinker, the raw materials comprise calcareous (lime-bearing) and argillaceous (claylike) materials. The calcareous material may be quarried limestone, dredged marine shells or marl. The argillaceous materials could be clay, slate, shale, or special blast-furnace slags. As in a typical mill, the raw materials are preferably pulverized and handled either as wet suspension or as dry solids. The plant of the invention may use a dry process or a wet process. In the dry process, the pulverized materials are dried in a kiln drier and mixed in the proper proportion. In a wet process, the materials are processed as a wet slurry.

The kiln (12) has an inlet (14) for receiving the raw materials, an outlet (16) for discharging the cement clinker and a gas outlet (18) connected to a chimney stack (19) for discharging an exhaust gas containing CO_2 .

The plant (10) further comprises a bioreactor (20) for catalysing the hydration of the CO_2 contained in the exhaust gas into bicarbonate ions and hydrogen ions. The bioreactor (20) is preferably as described in WO9855210 in the name of the applicant. It has a gas inlet (22) for receiving at least a portion of the exhaust gas, preferably all the exhaust gas from the kiln (10) and a liquid inlet (24) for receiving an aqueous liquid. Although any liquid containing water could be used, it is easier to simply use water. The bioreactor (20) further includes a reaction chamber (26) in fluid communication with the gas inlet (22) and the liquid inlet (24), the reaction chamber (26) containing therein enzymes capable of catalysing the hydration of dissolved CO_2 (meaning aqueous CO_2) into bicarbonate ions and hydrogen ions. The enzymes may be in a free state or it may be immobilized on appropriate supports. A liquid outlet (28) in fluid communication with the reaction chamber (26) is provided for discharging a solution of bicarbonate ions and hydrogen ions.

15 The plant (10) further comprises means, preferably a reaction reservoir (30), for reacting the bicarbonate ions obtained in the bioreactor (20) with metal ions to precipitate a carbonate of said metal.

According to a preferred aspect, the bicarbonate ions are reacted with Ca^{++} ions obtained by the dissolution in the reservoir (30) of a material selected from the group consisting of CaCl_2 , cement kiln dust and sea salts. In such a case, the precipitate obtained, CaCO_3 , is advantageously recycled in the process as a raw material fed to the kiln (10). As will be apparent for any person in the field, the plant (10) in such a case comprises means for transferring the precipitate CaCO_3 into the inlet (14) of the kiln (10). As for example, in a wet process, the precipitate could be transferred directly into the kiln by means of conventional piping and pump systems, or by means of any other transfer system known in the art. In a dry process, the precipitate will preferably be dried before being transferred to the kiln (10).

30 The plant also preferably comprises cleansing means, such as a filter (32), for cleansing the exhaust gas coming from the cement chimney (19) of kiln (10). The filter (32) helps removing the CKD from the exhaust gas, which CKD may advantageously

- be used in the process for precipitating the CaCO_3 . As apparent to any person in the art, in such a case, the plant (10) comprises means for transferring the exhaust gas from the kiln to the cleansing means, and means for transferring the clean exhaust gas from the cleansing means to the bioreactor (20). These transfer means may be, for example, any appropriate conduct systems.

Detailed Description of the process

As defined above, and referring to figure 1, the process for producing cement clinker, comprising the steps of:


- 10 a) providing a mixture of ground calcareous materials and ground argillaceous materials as defined above;
- b) heating the mixture of step a) to a temperature sufficient to calcine and fuse the ground materials to form the cement clinker, and thereby producing an exhaust gas containing CO_2 ;
- 15 c) catalysing the hydration of at least a portion of the CO_2 contained in the exhaust gas and producing a solution containing bicarbonate ions and hydrogen ions; and
- d) adding to the solution obtained in step c) metal ions, and adjusting the pH of the solution to precipitate a carbonate of said metal.

20

The solution containing biocarbonate ions is preferably reacted with a solution containing Ca^{++} ions so to form CaCO_3 which can be recycled into the process as a first class raw material.


- 25 The temperature sufficient to calcine and fuse the materials to form cement clinker is 1400°C or more, meaning substantially 1400°C or more.

The current industrial process for cement production relies on the following chemical reactions :



The process initiates CO_2 emissions from three different sources: two from combustion and the other from the breakdown of CaCO_3 into CaO and CO_2 . The

- 5 proposed complementary process intends, first, to transform CO_2 according to the following bioreaction:




- 10 Secondly, to set a reaction between the ion HCO_3^- and an ion such as calcium (Ca^{2+}) which can be found for example in calcium chloride (CaCl_2), CKD, sea salts or others CaCO_3 will precipitate easily in an aqueous solution containing HCO_3^- and Ca^{++} ions.

Thirdly, this CaCO_3 can be used as first class raw material in the cement production

- 15 process.

Estimates of the quantities involved are calculated using the molecular weights converted into tonnes.




tonnes : 44 t 18 t 1 t 61 t

- 20 $\text{HCO}_3^- \rightarrow \text{CO}_3^{2-} + \text{H}^+ (\text{Carbonate})$

tonnes : 61 t 60 t 1 t



tonnes : 66 t 40 t 26 t



- 25 tonnes : 40 t 60 t 100 t

The flow chart of figure 1 is more explicit in showing the main steps occurring in the cement production. The three CO_2 emissions are identified. Two important sources are related to the energy required to heat, while the other is due to the lime production (CaO). All these emissions proceed to the chimney stack (19).

Assuming the bioreactor (20) to be 100 % efficient, 44 tonnes of CO_2 would produce 60 tonnes of carbonate ions. This amount of carbonate added to 66 tonnes of CaCl_2 could generate 100 tonnes of CaCO_3 .

The enzymes used in the bioreactor could be any enzyme capable of catalysing the hydration of CO_2 into hydrogen ions and bicarbonate ions, for example, carbonic anhydrase or analogue thereof.

The calcium ions can be provided by using any chemical compound containing calcium and being capable of providing calcium ions in solution, for example, CaCl_2 , sea salt, cement kiln dust or others.

Tables 2 and 3 show preliminary results of leaching essays performed on Cement Kiln Dust plant refuse and subsequent precipitation of bicarbonate ions by addition of filtered leachate. Analyses of major ion concentrations during the first leaching essay with 50 g of CKD in 500 ml water are shown in table 2. The most concentrated ions are potassium, calcium, sodium and chlorides, whereas aluminium, magnesium and baryum are weakly concentrated. A leaching pH of 12.33 allowed for recovery of a small portion of calcium present in the refuse. In spite of the calcite formation potential of this solution being 1.9 g calcite per liter, this cation dissolution potential may be increased by the variation of experimental parameters such as the pH, the temperature, the solid-liquid contact time and the solid concentration per unit of volume of water.

Table 2 Major ion concentrations in CDK refuse leachate

Ions	Mole / L
K	2.15E-01
Ca	1.90E-02
Na	2.30E-02
Cl ⁻	6.29E-02
Al	1.48E-05
Mg	1.67E-06
Ba	8.03E-06
PH	12.33

Further essays permitted to validate the precipitation potential of carbonate ions by the addition of refuse leachate to a sodium bicarbonate solution. In these essays, the pH of the leachate was not adjusted, rather, amounts of solids from the refuse were simply added in a volume of distilled water. The refuse added to water was mixed with agitation for two hours on a mechanical table agitator at room temperature of 22 °C. Conductivity and pH measurements of the leachate were taken from samples before the precipitation step.

The following table shows the results of leaching essays by addition of 50, 100 and 500 g of CKD to 500 ml of pure water. Firstly, the final leaching pH of sample PR1 (50 g CKD /500 ml) was 12.56 and that of the previous essay with the same refuse:water ratio was 12.33. This could explain precipitation of the mass at 0.7 g/L which is slightly inferior to the 0.95 g/L precipitation potential of calcite (1.9 g/L/2; dilution factor) calculated according to the 0.019 mol Ca/L in the leachate. The solid mass increase in the volume of water (samples PR2 and PR3) allowed for an increase of the resulting precipitate mass although not in a proportional fashion. The very alkaline pH during leaching might explain this phenomenon. Even if the conductivity of sample PR3 is higher than for PR1 and PR2, the 0.25 g/L precipitate mass is much weaker than the others. Chemical analyses will allow characterization of solid samples. Finally, all samples showed an effervescence reaction upon addition of diluted hydrochloric acid, which indicates precipitation of carbonate ions. Electron microscopy analyses of the sample, as well as mineral identification through X-ray diffraction confirmed pure calcite precipitation into cubic crystals with an

average edge or $5\mu\text{m}$.

Table 3 Results of preliminary refuse leaching and bicarbonate ion precipitation essays

Sample No	CKD mass in 500 ml water	Conductivity of leachate mS/cm	pH of the leachate	NaHCO_3 concentration added mol/L	Mass of precipitate obtained g/L
PR1A	50	37.2	12.56	0.25	0.712
PR1B	50	37.2	12.56	0.25	0.721
PR1C	50	37.2	12.56	0.25	0.724
PR2A	100	51.8	12.79	0.25	0.851
PR2B	100	51.8	12.79	0.25	0.826
PR2C	100	51.8	12.79	0.25	0.830
PR3A	500	94.6	13.13	0.25	0.247

Consequently, recovery of CO_2 from the fabrication of cement and its transformation into bicarbonate ions in an enzymatic reactor, followed by the bicarbonate ion precipitation into calcite, through addition of leached refuse from cement plants as a source of calcium, and integration of the calcite as raw matter into the cement fabrication process allows for the recovery of CO_2 responsible for the greenhouse effect and climatic changes. The perpetual cycle of the present invention therefore allows the elimination of CO_2 emissions from cement plants into the atmosphere and the production of a reusable by-product in the cement fabrication process.

The precipitation of bicarbonate ions, resulting from the transformation of CO_2 , may also be achieved by the addition of external chemical salts, such as calcium chloride, magnesium chloride, baryum chloride, sea salt etc. Carbonated precipitates of these metals (CaCO_3 - calcite, MgCO_3 - magnesite, BaCO_3 - witherite, $\text{CaMg}(\text{CO}_3)_2$ - dolomite and others) were obtained in laboratory essays their optimal precipitation pH determined.

For example, calcite and witherite were obtained at a pH as low as 8 and the increase of pH did not affect the composition of the precipitate. The concentration in magnesite however is optimal at a pH between 10 and 11 only. Precipitation by addition of sea salt is optimal at pH 10 but tends to form hydroxocomplexes with

available cations at very alkaline pH. The essays were carried out with solutions of 0.1 mol/L in cations and bicarbonates, which in theory correspond to 10 g/L calcite, 8.4 g/L magnesite and 19.7 g/L witherite.

Experimentation permitted to obtain up to 9.7 g/L calcite, 6.9 g/L magnesite and 19.4 g/L witherite. With sea salt, the maximal precipitate mass obtained was 5.3 g/L halite (NaCl) by evaporation during sample drying, hydromagnesite ($\text{Mg}_5(\text{CO}_3)_4(\text{OH})_2 \cdot 4\text{H}_2\text{O}$), dolomite (CaMgCO_3)₂ and aragonite (CaCO_3).

Also preferably, the process may comprise, prior to feeding the bioreactor with the CO₂ emissions, a treatment unit for purifying the CO₂ emissions and removing waste particles from the same, such as dust, etc.

Although a preferred embodiment of the present invention has been described in detail herein and illustrated in the accompanying drawings, it is to be understood that the invention is not limited to this precise embodiment and that various changes and modifications may be effected therein without departing from the scope or spirit of the present invention.

WHAT IS CLAIMED IS:

1. A process for producing cement clinker, comprising the steps of:

5 a) providing a mixture of ground calcareous materials and ground argillaceous materials;

b) heating the mixture of step a) to a temperature sufficient to calcine and fuse the ground materials to form the cement clinker, and thereby producing an exhaust gas containing CO_2 ;

10 c) catalysing the hydration of at least a portion of the CO_2 contained in the exhaust gas and producing a solution containing bicarbonate ions and hydrogen ions; and

d) adding to the solution obtained in step c) metal ions, and adjusting the pH of the solution to precipitate a carbonate of said metal.

15 2. A process as claimed in claim 1, wherein said hydration is performed in the presence of an enzyme capable of catalysing the hydration of dissolved CO_2 into hydrogen ions and bicarbonate ions.

20 3. A process as claimed in claim 1 wherein, the metal ions are Ca^{++} and the carbonate is CaCO_3 .

4. A process as claimed in claim 3, comprising, after step d), the step of:

e) recycling the CaCO_3 obtained in step d) into the process by adding the CaCO_3 to the mixture of step a).

25

5. A process as claimed in claim 2, wherein the enzyme used in step c) is carbonic anhydrase or an analogue thereof.

6. A process as claimed in claim 5, wherein step c) comprises the steps of

30 -feeding liquid H_2O and at least a portion of the exhaust gas into a bioreactor containing therein a reaction chamber filled with said carbonic anhydrase immobilized on a support.

7. A process as defined in claim 3, wherein the ions Ca^{++} are obtained from the dissolution of a material selected from the group consisting of CaCl_2 , cement kiln dust and sea salts.

5

8. A process as defined in claim 1, wherein the calcareous materials are selected from the group consisting of limestone, marine shells and marl.

10

9. A process as defined in claim 1 wherein the argillaceous materials are selected from the group consisting of clay, slate, sand, shale, and blast-furnace slags.

10. A process as claimed in claim 1, wherein the mixture of step a) further comprises one or more material selected from the group consisting of aluminium, iron and chemical admixture.

15

11. A process as claimed in claim 1, wherein the metal ions is selected from the group consisting of Ca^{++} , Mg^{++} , Ba^{++} , CaMg^{++} and Na^{+} .

20

12. A process as claimed in claim 1, comprising, prior to step c) of hydration, the step of:

-cleansing the exhaust gas for removing waste particles.

13 A process as claimed in claim 1, wherein said temperature sufficient to calcine and fuse the ground materials is at least 1400°C .

25

14. A plant for producing cement clinker, comprising:

-a kiln for burning raw materials suitable for producing cement clinker, the kiln having an inlet for receiving the raw materials, an outlet for discharging the cement clinker and a gas outlet for discharging an exhaust gas containing CO_2 ;

30

-means for catalysing the hydration of the CO_2 contained in the exhaust gas into bicarbonate ions and hydrogen ions;

means for reacting the bicarbonate ions with metal ions to precipitate the carbonate of said metal.

- 15 A plant as claimed in claim 14, wherein said metal ions are Ca^{++} and the carbonate is CaCO_3 and wherein the plant further comprises:

means for transferring the precipitate CaCO_3 into the inlet of the kiln.


16. A plant as claimed in claim 14, wherein the means for catalysing the hydration of the CO_2 comprises a bioreactor comprising :

- 10 -a gas inlet for receiving at least a portion of the exhaust gas from the kiln;
 -a liquid inlet for receiving an aqueous liquid,
 -a reaction chamber in fluid communication with the gas inlet and the liquid inlet, the reaction chamber containing therein immobilized enzymes
15 capable of catalysing the hydration of dissolved CO_2 into bicarbonate ions and hydrogen ions; and
 - a liquid outlet in fluid communication with the reaction chamber for discharging a solution of bicarbonate ions and hydrogen ions.

- 20 17. A plant as claimed in claim 14, wherein the means for reacting the bicarbonate ions with metal ions is a reaction tank.

18. A plant as claimed in claim 14, comprising;

- cleansing means for cleansing the exhaust gas;
25 -means for transferring the exhaust gas from the kiln to the cleansing means;
and
 -means for transferring the clean exhaust gas from the cleansing means to the catalysing means. .

FIG. 1

INTERNATIONAL SEARCH REPORT

 national Application No
 PCT/CA 02/00517

 A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 C04B7/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 C04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 37 29 695 A (PASSAMAQUODDY TRIBE) 17 March 1988 (1988-03-17) page 4, line 32 - line 63; example 1	1, 14
A	US 3 925 534 A (SINGLETON FRANK HENRY ET AL) 9 December 1975 (1975-12-09) column 3, line 3 - column 4, line 9	1, 14

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the International filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another claim or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Z" document member of the same patent family

Date of the actual completion of the international search

1 August 2002

Date of mailing of the international search report

08/08/2002

Name and mailing address of the ISA

 European Patent Office, P.B. 5018 Patentamt 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Rauscher, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

National Application No

PCT/CA 02/00517

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 3729695	A	17-03-1988	US 4716027 A	29-12-1987
			AT 396433 B	27-09-1993
			AT 222387 A	15-01-1993
			AU 593681 B2	15-02-1990
			AU 7796187 A	17-03-1988
			BE 1002111 A4	10-07-1990
			BR 8704632 A	26-04-1988
			CA 1302049 A1	02-06-1992
			CH 676555 A5	15-02-1991
			CN 87105795 A , B	13-07-1988
			CN 1049294 A	20-02-1991
			DE 3729695 A1	17-03-1988
			DK 461487 A	06-03-1988
			ES 2005293 A6	01-03-1989
			FR 2603500 A1	11-03-1988
			GB 2199314 A , B	06-07-1988
			GR 871373 A1	12-01-1988
			IT 1223643 B	29-09-1990
			JP 63123843 A	27-05-1988
			KR 9312036 B1	23-12-1993
			MX 163666 B	11-06-1992
			NZ 221664 A	26-09-1990
			TR 24746 A	09-03-1992
			YU 163587 A1	31-10-1989
			ZA 8706626 A	25-05-1988
US 3925534	A	09-12-1975	GB 1426335 A	25-02-1976
			JP 49086419 A	19-08-1974